## NSN 5930-01-070-2461

Pressure Switch - Page 1 of 2



5
View Online at https://aerobasegroup.com/nsn/5930-01-070-2461
Overall Length:
5.344 inches
Overall Height:
1.906 inches
Overall Width:
4.500 inches
Body Length:
3.500 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Longest Horizontal Distance Between Mounting Centers:
4.250 inches
Longest Vertical Distance Between Mounting Centers:
2.875 inches
End Application:
W/s: ticonderoga class cg 47; virginia class cgn 41
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -55.0 degrees celsius and 85.0 degrees celsius
Mounting Method:
Flange and unthreaded hole
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
30.00 pounds per square inch gage
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Terminal Type:

Screw

**Contact Load Current Rating:** 

5.0 amperes resistive load third voltage

**Contact Adjustment Range:** 

+0.00/+20.00 actuation point pounds per square inch gage

## NSN 5930-01-070-2461

Pressure Switch - Page 2 of 2

Fiig: A048b0



Contact Adjustment Type:	
Internal actuation point hex nut	
Contact Stimulus Rating:	
1.00 differential point pounds per square inch gage and 3.50 differential point pounds per square inch gage	
Contact Voltage Rating In Volts:	
48.0 dc at sea level third voltage	
Pressure Connector Type:	
Plain, threaded internal single connection	
Special Features:	
Weapon system essential	
Frequency In Hertz:	
60.0 single voltage	
Thread Series Designator:	
Npt single pressure connection	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	