

View Online at <https://aerobasegroup.com/nsn/5930-01-070-2645>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof and corrosion resistant

**Overall Length:**

1.310 inches

**Overall Height:**

2.217 inches

**Overall Width:**

0.750 inches

**Bushing Length:**

0.469 inches

**Body Length:**

1.310 inches

**Body Width:**

0.750 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Height:**

0.688 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Actuator Color:**

Natural single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Qr66-85 21617

**Mounting Surface To Terminal End Distance:**

1.060 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0