

View Online at <https://aerobasegroup.com/nsn/5930-01-070-2645>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof and corrosion resistant

Overall Length:

1.310 inches

Overall Height:

2.217 inches

Overall Width:

0.750 inches

Bushing Length:

0.469 inches

Body Length:

1.310 inches

Body Width:

0.750 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Height:

0.688 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Qr66-85 21617

Mounting Surface To Terminal End Distance:

1.060 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0