## NSN 5930-01-070-3571

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-070-3571
Thread Class:
2b single pressure connection
Overall Length:
5.625 inches
Overall Width:
2.875 inches
Body Length:
4.625 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
5.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
20.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw

**Contact Load Current Rating:** 

3.2 amperes resistive load first voltage

**Contact Adjustability:** 

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:** 

+2.00/+30.00 actuation point inches of vacuum and +1.30/+26.00 deactuation point inches of vacuum

**Contact Adjustment Type:** 

External deactuation point screw and external actuation point screw

## NSN 5930-01-070-3571

Pressure Switch - Page 2 of 2



## **Contact Voltage Rating In Volts:**

550.0 ac at sea level first voltage

## **Pressure Connector Type:**

Plain, threaded internal single connection

**Special Features:** 

0.250 in. Vent hole in box

**Thread Series Designator:** 

Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0