NSN 5930-01-070-3574

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-070-3574

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

3.105 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.100 inches

Individual Section Quantity:

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

7 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Shaft Flat/slot Angular Location:

252.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 each section

NSN 5930-01-070-3574Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:
7 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Makes before breaks 2nd section rear
Switch Actuator Positioning Increment:
36.0 degrees single actuator
Detent Rotational Torque Range:
+16.000/+80.000 inch-ounces single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load ac at sea level
Precious Material And Location:
Common terminal surfaces gold and rotor contact, stator contacts and terminals silver
Precious Material:
Gold and silver
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0