

View Online at <https://aerobasegroup.com/nsn/5930-01-070-3857>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.412 inches

**Body Length:**

0.542 inches

**Body Width:**

0.171 inches

**Body Height:**

0.616 inches

**Unthreaded Mounting Hole Diameter:**

0.094 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.382 inches

**Switch Actuator Quantity:**

1

**Actuator Length:**

2.000 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.125 inches

**Actuator Free Position Height:**

1.500 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Uninclosed

**Pile-up Contact Form Arrangement:**

1a single position

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

**Switch Release Force:**

7.0 grams

**Switch Actuating Force:**

8.0 grams

**Actuator Movement:**

14.0 pretravel degrees and 8.0 overtravel degrees and 0.203 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac

**Special Features:**

Mounting plate 54418 part no. 460923-1; insulator 54418 part no. 460928; connector 81312 part no. Jf1p1s32a.

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0