

View Online at <https://aerobasegroup.com/nsn/5930-01-070-4696>

Thread Class:

2a single mounting facility

Thread Length:

0.355 inches single mounting facility and 0.395 inches single mounting facility

Overall Length:

Between 2.685 inches and 2.765 inches

Overall Diameter:

Between 1.000 inches and 1.030 inches

Individual Section Quantity:

1

End Application:

F-16 oper flight trainer

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

36 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

Keyway is 0.069 in. Wide by 0.036 in. Deep measured from a 0.375 dia; compressible panel seal; bushing is 0.375 in. Length; threads are 0.3750-32 unef-2a

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0