# NSN 5930-01-070-4696

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-070-4696

# Thread Class:

2a single mounting facility

# Thread Length:

 $0.355 \ \text{inches} \ \text{single} \ \text{mounting} \ \text{facility} \ \text{and} \ 0.395 \ \text{inches} \ \ \text{single} \ \text{mounting} \ \text{facility}$ 

# Overall Length:

Between 2.685 inches and 2.765 inches

# **Overall Diameter:**

Between 1.000 inches and 1.030 inches

# Individual Section Quantity:

1

#### **End Application:**

F-16 oper flight trainer

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 single section front

#### \_\_\_\_\_

Throw Quantity:

36 single section front

## Mounting Method:

Threaded bushing single mounting facility

## Thread Size:

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

4 single actuator

#### **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section front

#### **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

## **Special Features:**

Keyway is 0.069 in. Wide by 0.036 in. Deep measured from a 0.375 dia; compressible panel seal; bushing is 0.375 in. Length; threads are

0.3750-32 unef-2a

#### Style Designator:

Tap, circular, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5930-01-070-4696

Rotary Switch - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A052b0

