

View Online at <https://aerobasegroup.com/nsn/5930-01-070-5886>

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Thread Length:

0.500 inches single pressure connection

Hazardous Locations/environmental Protection:

Dusttight

Overall Length:

3.250 inches

Body Length:

2.170 inches

Overall Diameter:

1.380 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit

Mounting Method:

Input port

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+400.00/+1000.00 actuation point pounds per square inch gage and +400.00/+1000.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

125.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0