## NSN 5930-01-070-5886

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-070-5886

**Thread Class:** 3b single pressure connection **Inside Diameter:** 0.438 inches single connection Thread Length: 0.500 inches single pressure connection **Hazardous Locations/environmental Protection:** Dusttight **Overall Length:** 3.250 inches **Body Length:** 2.170 inches **Overall Diameter:** 1.380 inches **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit **Mounting Method:** Input port **Features Provided:** Electrical box connector Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Thread Size:** 0.438 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage **Contact Adjustability:** Deactuation point adjustable and actuation point adjustable **Contact Adjustment Range:** +400.00/+1000.00 actuation point pounds per square inch gage and +400.00/+1000.00 deactuation point pounds per square inch gage **Contact Adjustment Type:** 

**Contact Stimulus Rating:** 

125.00 differential point pounds per square inch gage

External deactuation point screw and external actuation point screw

## NSN 5930-01-070-5886

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Liquid Style Designator: Cylindrical Thread Series Designator: Unf single pressure connection Shelf Life: N/a Unit Of Measure: ---

**Demilitarization:** 

No Fiig: A048b0