## NSN 5930-01-071-0407

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:** 

Bushing mounted

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5930-01-071-0407

Fungus proof and salt spray resistant and vibration resistant and waterproof

2.490 inches
Overall Height:
1.015 inches
Overall Width:
1.015 inches
Body Diameter:
1.015 inches
Bushing Length:
1.000 inches
Body Length:
1.115 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.150 inches
Actuator Height:
0.375 inches
Actuator Free Position Height:
1.375 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
240.0 ounces
Switch Actuating Force:
Between 288.0 ounces and 368.0 ounces
Actuator Movement:
Between 0.055 pretravel inches and 0.040 overtravel inches and 0.040 differential inches

## NSN 5930-01-071-0407

Sensitive Switch - Page 2 of 2



Contact Load C	<b>Current Rating</b>	At Maximum	Rated '	Voltage:
----------------	-----------------------	------------	---------	----------

10.000 amperes resistive dc and 5.000 amperes inductive dc

**Special Features:** 

Red connector ring

**Terminal Type And Quantity:** 

8 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0