

View Online at <https://aerobasegroup.com/nsn/5930-01-071-1734>

**Hazardous Locations/environmental Protection:**

Dustproof and watertight

**Overall Length:**

5.188 inches

**Overall Width:**

2.812 inches

**Body Height:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Capillary Tube Length:**

120.0 inches

**Bulb Length:**

14.500 inches

**Bulb Diameter:**

1.250 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Operating Temperature Rating:**

245.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 two circuit, two positions momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes resistive load fourth voltage

**Contact Adjustability:**

Deactuation point not adjustable, manual reset and actuation point adjustable

**Contact Adjustment Range:**

+60.00/+130.00 actuation point degrees fahrenheit

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0