

View Online at <https://aerobasegroup.com/nsn/5930-01-071-1755>

**Thread Class:**

2a single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

2.281 inches

**Overall Height:**

1.890 inches

**Overall Width:**

1.890 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

1.156 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

600.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes inductive load highest dc voltage rating at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0