

View Online at <https://aerobasegroup.com/nsn/5930-01-071-3182>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.965 inches

First Flat Length:

0.250 inches 2nd actuator

Flat Height:

0.216 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.562 inches 1st actuator

Overall Diameter:

1.344 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

270.0 degrees from nonturn device all actuators

Switch Actuator Indexing Position Quantity:

5 2nd actuator

Shaft Type:

Round, flatted all actuators

Terminal Type:

Clip

Switch Actuator Positioning Increment:

90.0 degrees 1st actuator

Detent Rotational Torque Range:

+0.800/+4.000 inch-pounds all actuators

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Terminals and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0