

View Online at <https://aerobasegroup.com/nsn/5930-01-072-1446>

Hazardous Locations/environmental Protection:

Dustproof

Overall Width:

1.000 inches

Body Length:

2.188 inches

Body Height:

2.688 inches

Distance Between Mounting Facility Centers:

0.688 inches

Capillary Tube Length:

36.0 inches

End Application:

4120-00-998-6673

Pressure Switch Type:

Gage

Temperature Sensing Element Type:

Capillary tube

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Capillary tube end seal connection

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

7.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

10.00 actuation point pounds per square inch gage and 23.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

277.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/mounting lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0