

View Online at <https://aerobasegroup.com/nsn/5930-01-072-2249>

Thread Class:

3a single pressure connection

Thread Length:

0.282 inches single pressure connection

Overall Length:

3.500 inches

Outside Diameter:

0.437 inches single connection

Body Length:

2.260 inches

Overall Diameter:

1.380 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -17.0 degrees celsius and 70.0 degrees celsius

Mounting Method:

Terminal

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch gage

Thread Size:

0.437 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

4.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

100.00 actuation point pounds per square inch gage and 225.00 deactuation point pounds per square inch gage and 25.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0