# NSN 5930-01-072-2834

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-072-2834

## **Thread Class:**

3b single pressure connection

## **Overall Length:**

4.840 inches

# **Overall Diameter:**

1.700 inches

#### **Unthreaded Mounting Hole Diameter:**

0.223 inches

## **Distance Between Mounting Facility Centers:**

1.120 inches

## Pressure Switch Type:

Gage

## **Operating Tempurature Rating:**

Between 275.0 degrees fahrenheit and -65.0 degrees fahrenheit

#### Mounting Method:

Unthreaded hole

## Features Provided:

Hermetically sealed case

# Thready Qty Per Inch (tpi):

20 single pressure connection

#### **Contact Action Stimulus:**

Increase

#### **Proof Pressure:**

4500.00 pounds per square inch

#### **Thread Size:**

0.438 inches single pressure connection

#### **Mounting Facility Pattern:**

Two position in-line

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

#### **Sensing Element Burst Pressure:**

7500.00 pounds per square inch

#### **Terminal Type:**

Connector, receptacle

# **Contact Load Current Rating:**

4.0 amperes resistive load single voltage and 2.0 amperes inductive load single voltage

#### **Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

#### **Contact Stimulus Rating:**

1200.00 actuation point pounds per square inch and 700.00 deactuation point pounds per square inch and 500.00 differential point pounds

per square inch

# Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

# NSN 5930-01-072-2834

Pressure Switch - Page 2 of 2



# Pressure Connector Type:

Plain, threaded internal single connection

# Test Data Document:

81349-mil-s-9395 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unf single pressure connection

#### **Specification Data:**

81349-mil-s-9395/2 government specification

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A048b0