NSN 5930-01-072-2865

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-072-2865

Overall Length:
3.900 inches
Body Diameter:
1.440 inches
Overall Diameter:
1.870 inches
Unthreaded Mounting Hole Diameter:
0.210 inches
Pressure Switch Type:
Gage
Mounting Facility Circle Radius:
0.750 inches
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
1000.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Three position circular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Wire lead
Contact Load Current Rating:
5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+13.00/+80.00 actuation point pounds per square inch and +11.60/+72.00 deactuation point pounds per square inch
Contact Adjustment Type:
Internal actuation point tongue and internal deactuation point tongue
Contact Stimulus Rating:
30.00 actuation point pounds per square inch and 25.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

NSN 5930-01-072-2865

Pressure Switch - Page 2 of 2



Pr	ess	ure	Conn	ector	Typ	e
----	-----	-----	------	-------	-----	---

Plain, threaded external single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0