NSN 5930-01-072-3935

Pressure-thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-072-3935

Hazardous Locations/environmental Protection:					
Dustproof					
Overall Width:					
1.000 inches					
Body Length:					
2.188 inches					
Body Height:					
2.688 inches					
Distance Between Mounting Facility Centers:					
0.688 inches					
Capillary Tube Length:					
36.000 inches					
End Application:					
4120-00-998-6673					
Pressure Switch Type:					
Gage					
Tempurature Sensing Element Type:					
Capillary tube					
Mounting Method:					
Bracket and unthreaded hole					
Features Provided:					
Capillary tube end seal connection					
Contact Action Stimulus:					
Increase					
Mounting Facility Pattern:					
Two position in-line					
Nonpile-up Contact Arrangement:					
1 pole, single throw, normally open, momentary action					
Terminal Type:					
Screw					
Contact Load Current Rating:					
7.0 amperes resistive load second voltage					
Contact Adjustability:					
Deactuation point not adjustable and actuation point not adjustable					
Contact Stimulus Rating:					
250.00 actuation point pounds per square inch gage					
Contact Voltage Rating In Volts:					
277.0 ac at sea level second voltage					
Media For Which Designed:					
Gas or liquid					
Style Designator:					

otyle besignator.

Rectangular w/mounting lugs

NSN 5930-01-072-3935

Pressure-thermostatic Switch - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0