

View Online at <https://aerobasegroup.com/nsn/5930-01-072-3945>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.500 inches

Overall Height:

1.390 inches

Overall Width:

0.450 inches

Bushing Length:

0.437 inches

Body Length:

0.500 inches

Body Width:

0.450 inches

Body Height:

0.350 inches

Case Material:

Metal

Actuator Style:

Rectangular

Actuator Height:

0.448 inches

Actuator Width:

0.100 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 24.0 dc

End Application:

6625-01-016-8170

Mounting Surface To Terminal End Distance:

0.505 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contacts add terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0