## NSN 5930-01-072-3949

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-072-3949

Body Style:
Bushing/hole mounted
Overall Length:
0.565 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.188 inches
Overall Height:
1.053 inches
Overall Width:
0.313 inches
Bushing Length:
0.312 inches
Body Length:
0.565 inches
Body Width:
0.313 inches
Body Height:
0.431 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.130 inches
Actuator Height:
0.219 inches
Actuator Free Position Height:
0.219 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing and unthreaded hole
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit

4.0 ounces

**Switch Release Force:** 

## **NSN 5930-01-072-3949** Sensitive Switch - Page 2 of 2



Actuator Movement:  0.031 pretravel inches and 0.005 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  1.000 amperes resistive dc and 500.000 milliamperes inductive dc  Precious Material And Location:  Contacts gold  Thread Series Designator:  Uns  Terminal Type And Quantity: 3 turret  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A053a0	Switch Actuating Force:
0.031 pretravel inches and 0.005 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  1.000 amperes resistive dc and 500.000 milliamperes inductive dc  Precious Material And Location:  Contacts gold  Thread Series Designator:  Uns  Terminal Type And Quantity:  3 turret  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	22.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:  1.000 amperes resistive dc and 500.000 milliamperes inductive dc  Precious Material And Location:  Contacts gold  Thread Series Designator:  Uns  Terminal Type And Quantity:  3 turret  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Actuator Movement:
1.000 amperes resistive dc and 500.000 milliamperes inductive dc  Precious Material And Location: Contacts gold Thread Series Designator: Uns Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.031 pretravel inches and 0.005 overtravel inches and 0.002 differential inches
Precious Material And Location: Contacts gold Thread Series Designator: Uns Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Contact Load Current Rating At Maximum Rated Voltage:
Contacts gold Thread Series Designator: Uns Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.000 amperes resistive dc and 500.000 milliamperes inductive dc
Thread Series Designator:  Uns  Terminal Type And Quantity: 3 turret  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Precious Material And Location:
Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Contacts gold
Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
3 turret  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Uns
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	3 turret
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A053a0	Fiig:
	A053a0