

View Online at <https://aerobasegroup.com/nsn/5930-01-072-3949>

Body Style:

Bushing/hole mounted

Overall Length:

0.565 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Overall Height:

1.053 inches

Overall Width:

0.313 inches

Bushing Length:

0.312 inches

Body Length:

0.565 inches

Body Width:

0.313 inches

Body Height:

0.431 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.130 inches

Actuator Height:

0.219 inches

Actuator Free Position Height:

0.219 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and unthreaded hole

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

22.0 ounces

Actuator Movement:

0.031 pretravel inches and 0.005 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Precious Material And Location:

Contacts gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0