NSN 5930-01-072-9973

Pressure Switch - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5930-01-072-9973

Hazardous Locations/environmental Protection:
Corrosion resistant and vibration proof and watertight
Overall Diameter:
1.015 inches
End Application:
Weapon system-tank, abrams m-1
Pressure Switch Type:
Gage
Width Across Flats:
1.000 inches
Operating Tempurature Rating:
Between 60.0 degrees fahrenheit and 340.0 degrees fahrenheit
Mounting Method:
Input port
Contact Action Stimulus:
Decrease
Proof Pressure:
100.00 pounds per square inch gage
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Sensing Element Burst Pressure:
250.00 pounds per square inch gage
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
1.0 amperes resistive load single voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
2.00 actuation point pounds per square inch gage and 5.00 deactuation point pounds per square inch gage
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5930-01-072-9973

Pressure Switch - Page 2 of 2



Fiig:

A048b0