NSN 5930-01-072-9973

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-072-9973

Hazardous Locations/environmental Protection:

Corrosion resistant and vibration proof and watertight

Overall Diameter:

1.015 inches

End Application:

Weapon system-tank, abrams m-1

Pressure Switch Type:

Gage

Width Across Flats:

1.000 inches

Operating Tempurature Rating:

Between 60.0 degrees fahrenheit and 340.0 degrees fahrenheit

Mounting Method:

Input port

Contact Action Stimulus:

Decrease

Proof Pressure:

100.00 pounds per square inch gage

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

250.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

2.00 actuation point pounds per square inch gage and 5.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5930-01-072-9973

Pressure Switch - Page 2 of 2

Fiig: A048b0

