NSN 5930-01-073-2410

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-073-2410

Overall Length:
3.188 inches
Overall Height:
6.938 inches
Overall Width:
1.531 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Capillary Tube Length:
72.0 inches
Bulb Length:
3.688 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
4.219 inches
Longest Vertical Distance Between Mounting Centers:
1.875 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Base and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+100.00/+650.00 actuation point degrees fahrenheit and +100.00/+650.00 deactuation point degrees fahrenheit
Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

NSN 5930-01-073-2410

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:
250.0 ac at sea level single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:

N/a
Unit Of Measure:

__

Demilitarization:

No

Fiig:

A048b0