NSN 5930-01-073-2580

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-073-2580

Body Style:

Hole mounted

Overall Length:

3.040 inches

Overall Height:

2.720 inches

Overall Width:

2.125 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.330 inches

Actuator Height:

0.750 inches

Housing Height:

1.750 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.625 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 9.0 ounces and 24.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.219 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Modified by connecting an 8.000 in. No. 16 awg type b electric wire between pin a to the normally open terminal and pin b

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

NSN 5930-01-073-2580

Sensitive Switch - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

