## NSN 5930-01-073-2580

Sensitive Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-01-073-2580

Body Style:
Hole mounted
Overall Length:
3.040 inches
Overall Height:
2.720 inches
Overall Width:
2.125 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.330 inches
Actuator Height:
0.750 inches
Housing Height:
1.750 inches
Housing Width:
1.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.625 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 9.0 ounces and 24.0 ounces
Actuator Movement:
Between 0.078 pretravel inches and 0.219 overtravel inches and 0.002 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Special Features:
Modified by connecting an 8.000 in. No. 16 awg type b electric wire between pin a to the normally open terminal and pin b
Terminal Type And Quantity:
3 screw
Shelf Life:

## NSN 5930-01-073-2580

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0