## NSN 5930-01-073-2582

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-073-2582

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
1.860 inches
Overall Height:
0.880 inches
Overall Width:
0.880 inches
Bushing Length:
0.750 inches
Body Length:
0.420 inches
Case Material:
Metal
Actuator Diameter:
0.880 inches
Actuator Height:
0.280 inches
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc
Precious Material And Location:
Contact surfaces gold
Thread Series Designator:
Unef
Terminal Type And Quantity:

4 tab w/screw

## NSN 5930-01-073-2582

Push Switch - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0