

View Online at <https://aerobasegroup.com/nsn/5930-01-073-6118>

Thread Class:

2a single pressure connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

7.062 inches

Overall Height:

2.500 inches

Overall Width:

4.375 inches

Mounting Slot Width:

0.343 inches

Body Length:

5.250 inches

Longest Horizontal Distance Between Mounting Centers:

3.674 inches

Longest Vertical Distance Between Mounting Centers:

5.575 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and slot

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.562 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+4000.00/+6385.00 actuation point pounds per square inch gage and +4000.00/+6500.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0