NSN 5930-01-073-8789

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Corrosion resistant and moisture proof

Body Style:

Bushing mounted

Overall Length: 1.847 inches Overall Height: 0.750 inches Overall Width: 0.880 inches



View Online at https://aerobasegroup.com/nsn/5930-01-073-8789

Bushing Length:
0.560 inches
Body Length:
0.467 inches
Case Material:
Plastic
Actuator Diameter:
0.880 inches
Actuator Height:
0.430 inches
Actuator Color:
Green single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
D-963 engine 20551
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Rfi shielding
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
1 two circuit, two positions momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc
Thread Series Designator:
Uns

NSN 5930-01-073-8789

Push Switch - Page 2 of 2



Terminal	Type	And	Quantity:
-----------------	------	-----	-----------

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0