NSN 5930-01-073-8789

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Corrosion resistant and moisture proof

Body Style:

Bushing mounted

Overall Length: 1.847 inches Overall Height: 0.750 inches Overall Width: 0.880 inches



View Online at https://aerobasegroup.com/nsn/5930-01-073-8789

Bushing Length:				
0.560 inches				
Body Length:				
0.467 inches				
Case Material:				
Plastic				
Actuator Diameter:				
0.880 inches				
Actuator Height:				
0.430 inches				
Actuator Color:				
Green single actuator				
Maximum Voltage Rating In Volts:				
28.0 dc				
End Application:				
D-963 engine 20551				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Threaded bushing				
Features Provided:				
Rfi shielding				
Thready Qty Per Inch (tpi):				
24				
Thread Size:				
0.625 inches				
Nonpile-up Contact Arrangement:				
1 two circuit, two positions momentary single switch unit				
Contact Load Current Rating At Maximum Rated Voltage:				
10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc				
Thread Series Designator:				
Uns				

NSN 5930-01-073-8789

Push Switch - Page 2 of 2



Terminal	Type	And	Quantity:
-----------------	-------------	-----	-----------

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0