## NSN 5930-01-073-8884

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-073-8884

Thread Length:					
0.500 inches single threaded bushing					
Overall Length:					
21.600 inches					
Body Diameter:					
0.310 inches					
Body Length:					
1.475 inches					
End Application:					
1520-00-859-2670					
Tempurature Sensing Element Type:					
Bulb					
Width Across Flats:					
0.500 inches					
Mounting Method:					
Threaded bushing					
Features Provided:					
Electrical access port					
Thready Qty Per Inch (tpi):					
27 single threaded bushing					
Contact Action Stimulus:					
Increase					
Thread Size:					
Thread Size: 0.125 inches single threaded bushing					
0.125 inches single threaded bushing					
0.125 inches single threaded bushing  Nonpile-up Contact Arrangement:					
<ul><li>0.125 inches single threaded bushing</li><li>Nonpile-up Contact Arrangement:</li><li>1 pole, single throw, normally closed, momentary action</li></ul>					
<ul><li>0.125 inches single threaded bushing</li><li>Nonpile-up Contact Arrangement:</li><li>1 pole, single throw, normally closed, momentary action</li><li>Terminal Type:</li></ul>					
0.125 inches single threaded bushing  Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead					
O.125 inches single threaded bushing  Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:					
O.125 inches single threaded bushing  Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:  2.0 amperes resistive load single voltage					
O.125 inches single threaded bushing  Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:  2.0 amperes resistive load single voltage  Contact Adjustability:					
O.125 inches single threaded bushing  Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:  2.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable					
O.125 inches single threaded bushing  Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:  2.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:					
Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:  2.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit					
Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:  2.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:					
Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:  2.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  30.0 dc at sea level single voltage					
Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:  2.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  30.0 dc at sea level single voltage  Media For Which Designed:					
Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action  Terminal Type:  Wire lead  Contact Load Current Rating:  2.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  30.0 dc at sea level single voltage  Media For Which Designed:  Gas					

Npt single threaded bushing

## NSN 5930-01-073-8884

Thermostatic Switch - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_1	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0