NSN 5930-01-073-8884

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-073-8884

Thread Length:
0.500 inches single threaded bushing
Overall Length:
21.600 inches
Body Diameter:
0.310 inches
Body Length:
1.475 inches
End Application:
1520-00-859-2670
Tempurature Sensing Element Type:
Bulb
Width Across Flats:
0.500 inches
Mounting Method:
Threaded bushing
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
27 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
Thread Size: 0.125 inches single threaded bushing
0.125 inches single threaded bushing
0.125 inches single threaded bushing Nonpile-up Contact Arrangement:
0.125 inches single threaded bushingNonpile-up Contact Arrangement:1 pole, single throw, normally closed, momentary action
0.125 inches single threaded bushingNonpile-up Contact Arrangement:1 pole, single throw, normally closed, momentary actionTerminal Type:
0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead
O.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating:
O.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 2.0 amperes resistive load single voltage
O.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 2.0 amperes resistive load single voltage Contact Adjustability:
O.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 2.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
O.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 2.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 2.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit
Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 2.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 2.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level single voltage
Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 2.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level single voltage Media For Which Designed:
Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 2.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 251.00 actuation point degrees fahrenheit and 221.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level single voltage Media For Which Designed: Gas

Npt single threaded bushing

NSN 5930-01-073-8884

Thermostatic Switch - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0