NSN 5930-01-074-0654

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-074-0654

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
8.375 inches
Overall Height:
5.000 inches
Overall Width:
3.375 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.500 inches single actuator
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
6.375 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
4.000 inches single mounting facility
Switch Contact Basic Design:
Pile-up
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Cam actuated
Contact Voltage Rating In Volts:
600.0 highest dc voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Cam Actuated Switch Contact Arrangement:
2 two circuit, double break/double make, one position momentary each switch single section in-line
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Round single actuator
Nound Single actuator
Terminal Type:
-
Terminal Type:
Terminal Type: Screw
Terminal Type: Screw Contact Switching Action:

Contact Load Current Rating:

50.0 milliamperes resistive load lowest dc voltage rating at sea level

NSN 5930-01-074-0654

Rotary Switch - Page 2 of 2



Sty	_	п	201	ia	n	24	_	
-Oιy	ı	u	'C 3	ıy	"	aı	·	Ή.

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0