Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-074-0654

Hazardous Locations/environmental Protection: Dustproof **Overall Length:** 8.375 inches **Overall Height:** 5.000 inches **Overall Width:** 3.375 inches Shaft Diameter: 0.250 inches single actuator Shaft Length: 1.500 inches single actuator **Individual Section Quantity:** 1 Longest Horizontal Distance Between Mounting Centers: 6.375 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 4.000 inches single mounting facility Switch Contact Basic Design: Pile-up **Mounting Method:** Unthreaded hole single mounting facility Features Provided: Cam actuated **Contact Voltage Rating In Volts:** 600.0 highest dc voltage rating at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Cam Actuated Switch Contact Arrangement:** 2 two circuit, double break/double make, one position momentary each switch single section in-line **Switch Actuator Indexing Position Quantity:** 8 single actuator Shaft Type: Round single actuator **Terminal Type:** Screw **Contact Switching Action:** Breaks before makes single section in-line **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Contact Load Current Rating:** 50.0 milliamperes resistive load lowest dc voltage rating at sea level

## NSN 5930-01-074-0654

Rotary Switch - Page 2 of 2

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

