

View Online at <https://aerobasegroup.com/nsn/5930-01-074-1546>

Body Diameter:

1.120 inches

Overall Diameter:

1.440 inches

Unthreaded Mounting Hole Diameter:

0.200 inches

Distance Between Mounting Facility Centers:

1.120 inches

End Application:

Dehydrater filter dsc 01496

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 40.0 degrees fahrenheit and 130.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

225.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

45.00 actuation point pounds per square inch gage and 25.00 deactuation point pounds per square inch gage and 35.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0