

View Online at <https://aerobasegroup.com/nsn/5930-01-074-1546>

**Body Diameter:**

1.120 inches

**Overall Diameter:**

1.440 inches

**Unthreaded Mounting Hole Diameter:**

0.200 inches

**Distance Between Mounting Facility Centers:**

1.120 inches

**End Application:**

Dehydrater filter dsc 01496

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between 40.0 degrees fahrenheit and 130.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

225.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

1.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

45.00 actuation point pounds per square inch gage and 25.00 deactuation point pounds per square inch gage and 35.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0