NSN 5930-01-074-2663

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-074-2663

Overall Length:
5.188 inches
Overall Height:
6.844 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes resistive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:
0.50 differential point pounds per square inch gage and 1.00 differential point pounds per square inch gage

NSN 5930-01-074-2663

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts	s:
---------------------------------	----

550.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0