

View Online at <https://aerobasegroup.com/nsn/5930-01-074-3066>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Height:

0.781 inches

Overall Width:

1.130 inches

Body Length:

1.094 inches

Body Width:

0.781 inches

Body Height:

0.625 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.375 inches

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

F815a fl smlr 76301

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Pile-up Contact Form Arrangement:

2c single position

Switch Release Force:

30.0 grams

Switch Actuating Force:

50.0 grams

Actuator Movement:

Between 0.125 pretravel inches and 0.090 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0