NSN 5930-01-074-3066

Sensitive Switch - Page 1 of 2

50.0 grams



View Online at https://aerobasegroup.com/nsn/5930-01-074-3066

| Body Style: | |
|---|--|
| Hole mounted | |
| Hazardous Locations/environmental Protection: | |
| Dustproof | |
| Overall Length: | |
| 2.000 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| 0.875 inches | |
| Overall Height: | |
| 0.781 inches | |
| Overall Width: | |
| 1.130 inches | |
| Body Length: | |
| 1.094 inches | |
| Body Width: | |
| 0.781 inches | |
| Body Height: | |
| 0.625 inches | |
| Case Material: | |
| Plastic | |
| Unthreaded Mounting Hole Diameter: | |
| 0.114 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | |
| 0.406 inches | |
| Actuator Style: | |
| Roller arm | |
| Actuator Roller Diameter: | |
| 0.375 inches | |
| Maximum Voltage Rating In Volts: | |
| 250.0 ac | |
| End Application: | |
| F815a fl smlr 76301 | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Unthreaded hole | |
| Pile-up Contact Form Arrangement: | |
| 2c single position | |
| Switch Release Force: | |
| 30.0 grams | |
| Switch Actuating Force: | |

NSN 5930-01-074-3066

Sensitive Switch - Page 2 of 2



| Actuator | Movement: |
|----------|-----------|
|----------|-----------|

Between 0.125 pretravel inches and 0.090 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0