# NSN 5930-01-074-3068

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-074-3068

**Body Style:** 

Bushing/hole mounted

**Overall Length:** 

2.000 inches

**Overall Height:** 

2.690 inches

**Bushing Length:** 

0.450 inches

**Body Length:** 

1.250 inches

**Body Width:** 

0.500 inches

Body Height:

1.394 inches

**Case Material:** 

Metal

**Unthreaded Mounting Hole Diameter:** 

0.140 inches

Actuator Style:

Roller plunger

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.190 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

**Mounting Method:** 

Unthreaded hole

Thready Qty Per Inch (tpi):

32

**Thread Size:** 

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

17.0 ounces

**Actuator Movement:** 

Between 0.060 pretravel inches and 0.140 overtravel inches and 0.205 differential inches

# NSN 5930-01-074-3068

Sensitive Switch - Page 2 of 2



### Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

#### Thread Series Designator:

Uns

## Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

No

#### Fiig:

A053a0