## NSN 5930-01-074-3068

Sensitive Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-074-3068

Bushing/hole mounted
Overall Length:
2.000 inches
Overall Height:
2.690 inches
Bushing Length:
0.450 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
1.394 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Roller plunger
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.190 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
$2\ \text{pole},\ \text{single throw, normally open, momentary action single switch unit}$
Switch Release Force:
4.0 ounces
Switch Actuating Force:
17.0 ounces
Actuator Movement:

Between 0.060 pretravel inches and 0.140 overtravel inches and 0.205 differential inches

## NSN 5930-01-074-3068

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

4 quick disconnect, male

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0