

View Online at <https://aerobasegroup.com/nsn/5930-01-074-3389>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.667 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.483 inches single actuator

Individual Section Quantity:

2

Operating Temperature Range:

-65.0/+250.0 degrees fahrenheit

End Application:

Svo control cabinet 56232

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Flange single mounting facility

Features Provided:

Cam actuated

Contact Voltage Rating In Volts:

28.0 dc at sea level

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, both positions maintained each switch each section periphery

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section periphery

Detent Rotational Torque Range:

+0.500/+2.400 inch-ounces single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

7.0 amperes resistive load lowest ac voltage rating at sea level and 7.0 amperes inductive load lowest ac voltage rating at sea level

Style Designator:

Circular, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0