

View Online at <https://aerobasegroup.com/nsn/5930-01-074-3389>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.667 inches

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.483 inches single actuator

**Individual Section Quantity:**

2

**Operating Temperature Range:**

-65.0/+250.0 degrees fahrenheit

**End Application:**

Svo control cabinet 56232

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Flange single mounting facility

**Features Provided:**

Cam actuated

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Cam Actuated Switch Contact Arrangement:**

1 pole, double throw, both positions maintained each switch each section periphery

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Detent Rotational Torque Range:**

+0.500/+2.400 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

7.0 amperes resistive load lowest ac voltage rating at sea level and 7.0 amperes inductive load lowest ac voltage rating at sea level

**Style Designator:**

Circular, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0