## NSN 5930-01-074-3918

Thermostatic Switch - Page 1 of 2

46.00 deactuation point degrees fahrenheit

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5930-01-074-3918

2b all threaded hole	
Hazardous Locations/environmental Protection:	
Dusttight	
Overall Length:	
2.000 inches	
Overall Height:	
0.921 inches	
Body Diameter:	
1.181 inches	
Body Height:	
0.453 inches	
Distance Between Mounting Facility Centers:	
1.625 inches	
End Application:	
Svo control cabinet 56232	
Tempurature Sensing Element Type:	
Internal sensor	
Operating Tempurature Rating:	
65.0 degrees celsius and 0.0 degrees celsius	
Mounting Method:	
Bracket and threaded hole	
Features Provided:	
Electrical access port	
Thready Qty Per Inch (tpi):	
32 all threaded hole	
Contact Action Stimulus:	
Increase	
Thread Size:	
0.164 inches all threaded hole	
Mounting Facility Pattern:	
Two position in-line	
Nonpile-up Contact Arrangement:	
1 pole, double throw, one position momentary	
Terminal Type:	
Tab, solder lug	
Contact Load Current Rating:	
25.0 amperes resistive load second voltage	
Contact Adjustability:	
Deactuation point not adjustable and actuation point not adjustable	
Contact Stimulus Rating:	

34.00 actuation point degrees fahrenheit and 46.00 actuation point degrees fahrenheit and 34.00 deactuation point degrees fahrenheit and

## NSN 5930-01-074-3918

Thermostatic Switch - Page 2 of 2



<b>Contact Voltage Rating In Volts:</b>
240.0 ac at sea level first voltage
Media For Which Designed:
Gas
<b>Precious Material And Location:</b>
Contacts silver
Precious Material:
Silver
Style Designator:
Disc w/flange
Thread Series Designator:
Unc all threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A048b0