NSN 5930-01-074-3918

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-074-3918

Thread Class:

2b all threaded hole

Hazardous Locations/environmental Protection:

Dusttight

Overall Length:

2.000 inches

Overall Height:

0.921 inches

Body Diameter:

1.181 inches

Body Height:

0.453 inches

Distance Between Mounting Facility Centers:

1.625 inches

End Application:

Svo control cabinet 56232

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

65.0 degrees celsius and 0.0 degrees celsius

Mounting Method:

Bracket and threaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

25.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

34.00 actuation point degrees fahrenheit and 46.00 actuation point degrees fahrenheit and 34.00 deactuation point degrees fahrenheit and

46.00 deactuation point degrees fahrenheit

NSN 5930-01-074-3918

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Disc w/flange

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0