

View Online at <https://aerobasegroup.com/nsn/5930-01-074-5185>

Thread Length:

0.250 inches single mounting facility

Overall Height:

1.312 inches

Overall Width:

1.312 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

12 each section in-line

Mounting Method:

Threaded bushing single mounting facility

Cubic Measure:

1.690 cubic inches

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 dc at sea level

Cam Actuated Switch Contact Arrangement:

1 pole, single throw, both positions maintained each switch each section in-line

Switch Actuator Indexing Position Quantity:

12 single actuator

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

0.50 amperes resistive load highest dc voltage rating at sea level and 0.25 amperes inductive load highest dc voltage rating at sea level

Style Designator:

Circular wafer, bushing mount

Test Data Document:

11982-17362sb specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0