

View Online at <https://aerobasegroup.com/nsn/5930-01-074-5185>

**Thread Length:**

0.250 inches single mounting facility

**Overall Height:**

1.312 inches

**Overall Width:**

1.312 inches

**Individual Section Quantity:**

2

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

12 each section in-line

**Mounting Method:**

Threaded bushing single mounting facility

**Cubic Measure:**

1.690 cubic inches

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

500.0 dc at sea level

**Cam Actuated Switch Contact Arrangement:**

1 pole, single throw, both positions maintained each switch each section in-line

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

0.50 amperes resistive load highest dc voltage rating at sea level and 0.25 amperes inductive load highest dc voltage rating at sea level

**Style Designator:**

Circular wafer, bushing mount

**Test Data Document:**

11982-17362sb specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0