## NSN 5930-01-075-2932

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:** 

Bushing mounted

Corrosion resistant

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-075-2932

3.410 inches
Case Material:
Metal
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.310 inches
Housing Diameter:
1.000 inches
Housing Length:
2.156 inches
Housing Bushing Length:
0.340 inches
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
E3a aircraft 81205
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
144.0 ounces
Switch Actuating Force:
Between 192.0 ounces and 400.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and $3.000$ amperes inductive dc and $4.000$ amperes motor dc
Thread Series Designator:
Uns

## NSN 5930-01-075-2932

Sensitive Switch - Page 2 of 2



Termina	I Type	And	Quantity:
2 wire le	ad		

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0