# NSN 5930-01-075-6802

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-075-6802

#### **Thread Class:**

2b single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

2.984 inches

### **Overall Height:**

2.500 inches

### **Overall Width:**

1.500 inches

#### First Flat Length:

0.750 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

1.000 inches single actuator

## Individual Section Quantity:

5

### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### Throw Quantity:

3 each section rear

### **Mounting Facility Circle Radius:**

1.156 inches single mounting facility

### **Mounting Method:**

Base single mounting facility and threaded hole single mounting facility

#### **Features Provided:**

Actuator knob

### Thready Qty Per Inch (tpi):

24 single mounting facility

### **Thread Size:**

0.190 inches single mounting facility

## **Contact Voltage Rating In Volts:**

500.0 ac at sea level

## Mounting Facility Pattern:

Four position circular single mounting facility

## Switch Actuator Indexing Position Quantity:

3 single actuator

# NSN 5930-01-075-6802

Rotary Switch - Page 2 of 2



# Shaft Type:

Round, flatted, threaded hole single actuator

# **Terminal Type:**

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

**Contact Load Current Rating:** 

30.0 amperes resistive load dc at sea level

## Style Designator:

Tap, circuit selector

## Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unc single mounting facility

Specification Data:

81349-mil-s-15291 government specification

# Shelf Life:

N/a

# Unit Of Measure:

--

### Demilitarization:

No

```
Fiig:
```

A052b0